

Product List

Product code	Shatter proof	Security	UV cut	Solar control	Signal interference	Exterior	Scratch resistant coating	Privacy effect	Vision control	Green purchasing law	Width 970mm	Width 1250mm	Width 1550mm	Length	Production on order	Feature
X-1515	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				5/15		a film which appears translucent from the front (within the range of -15° and +15° from the viewing point)						
Y-2555	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				5/15		a film which appears translucent from one direction (within the range of +25° and +55° from the viewing point)						
Z-2555	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				5/15		a film which appears translucent from two parts in two directions (within the range of ±25° and ±55° from the viewing point)						
W-0055	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				5/15		a film which appears translucent from one direction (within the range of 0° and +55° from the viewing point)						

Film features and benefits

[Shatterproof]

This feature helps reduce scattering of fragments after glass fracture caused by an explosion, earthquake or other disasters.

- Effective in reducing scattering of glass shards
- Satisfy the scattering prevention performance prescribed in JIS A 5759 (shot bag test, interlayer displacement test).
- Improve penetration resistance, in addition to the scattering prevention performance prescribed by JIS A 5759.

[UV cut]

This feature helps block ultraviolet (UV) rays, which are harmful to human skin and can cause fading of interior furnishings. Ultraviolet rays also emanate from indoor fluorescent lighting, but the associated fading is significantly reduced compared to films without this feature.

[Vision control]

There is variable view control effect depending on the viewing angle